



MATERIAL: ALUMINUM 5052-H32
 THICKNESS: 3/16"
 FINISH: TIME SAVED, CLEAR IRIDITE

HOLES:
 0.210" DIA & C.S. 90°x 0.380" DIA QTY: 2
 ALL C.S. ON NEAR SIDE

WEIGHT: 5.1g

| | | | | | | | | | | |
|-----|--------------|----------|--|--|---|--|-------------|--------------|----------------|---------------------------------|
| REV | DESCRIPTION: | DATE | MUST BE RoHS COMPLIANT | DIMENSIONS ARE IN INCHES TOLERANCES ON DECIMALS: XXX ± 0.008" XX ± 0.012" | THIS DOCUMENT IS THE PROPERTY OF ABSOPULSE ELECTRONICS LTD. ITS CONTENTS ARE PROPRIETARY AND MAY NEITHER BE COPIED, REPRODUCED NOR ITS CONTENTS DISCLOSED TO OTHERS WITHOUT PRIOR WRITTEN AGREEMENT FROM ABSOPULSE ELECTRONICS LTD. | Title: CONNECTION BRACKET | | | ABSOPULSE | |
| A | NEW ISSUE | 15/04/14 | | ANGLES: ± 2° FRACTIONS: ± 1/64" UNLESS OTHERWISE STATED | | Part of: 3U2 3U3 & 3U4 SYSTEM REAR SIDE | | | | Date: APR.15.2014 |
| | | | EDGES & HOLES DEBURRED SURFACES FREE OF SCRATCHES | | | Drawn by: B.Z. | Checked by: | Approved by: | Revision: 1 | Drawing No: MDR 998 753-005A |