


5000VA Rugged, Industrial Quality Inverter with Sine Wave Output CSI 5K Series

- Sinusoidal output voltage
- Filtered input
- Cooling by internal fans
- Full electronic protection
- Field-proven design topology

**4 x 3U3:
6U(10.5") x 17"x 16"
chassis mount**



**3 x 3U7:
9U x 19"x 16"
rack-mount**



These photos show two of a range of package options available.
Mechanical size depends on input/output configuration.
Chassis-mount and 19" rack-mount versions available on most designs

This rugged, modular, DC/AC inverter system uses a microprocessor controlled field proven design to generate 5000VA output power. It is a mature product with a track record in numerous applications. The DC/DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC/AC inverter to generate the required AC output. The use of high frequency conversion ensures a compact construction and low weight. The configuration of modules for the system depends on the input/output required. Each interconnection between modules is made with a single pair of wires. Full electronic protection eliminates the possibility of failure due to abnormal operating conditions, including application errors. Low component count and the use of components with established reliability results in high MTBF. Cooling is by built-in fans, which draw air into the unit. The system is manufactured at our plant under strict quality control. Customized versions are also available.

SPECIFICATIONS

Input Voltage

24V, 36V, 48V, 125V, 250Vdc
+/-15% are standard
Consult factory for other inputs

Input Protection

Inrush current limiting
Varistors
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

According to the input voltage required by the standard
Output neutral is connected to the chassis internally
Floating output as option

Standards

Designed to meet
C22.2 No. 107.1 - 01,
UL 458 and EN60950

EMI

EN 55022 Class A
as a minimum

Output Voltage

115Vac @ 60Hz or
400Hz/43A rms continuous;
or 230Vac @ 50Hz/22A rms continuous.

Output neutral is connected to the chassis internally.
Isolated floating output optional
Consult factory for other output requirements

Output Wave Form

Sinusoidal

Total Harmonic Distortion

Less than 5% at full load

Line/Load Regulation

Maximum $\pm 6\%$ from no load to full load.
 $\pm 2\%$ load regulation option is available

Load Crest Factor

Maximum 2.5 at 90% load

Output Noise

High frequency ripple is less than 500mVrms (20MHz BW)

Output Overload Protection

Current limiting with short circuit protection.
Thermal shutdown with automatic recovery in case of insufficient cooling

Output Overvoltage Protection

140Vac (for 115Vac output) or
280Vac (for 230Vac output) by internal supply voltage limiting

Efficiency

Depends on input and output voltage combination.
Typically 76% at full load

Operating Temperature Range

0° C to +50° C for full specification
Extended temperature ranges available

Temperature Drift

0.05% per °C over operating temperature range

Cooling

Built-in fans drawing air into the unit

Environmental Protection

Basic ruggedizing
Full ruggedizing and conformal coating as option

Humidity

5 - 95% non-condensing

MTBF

Min. 95,000 hours at 45°C
Demonstrated MTBF is significantly higher
Fans excluded

Indicators

None
Available as an option

Control Input

None
Available as an option

Alarm Output

None
Available as an option

Package/Dimensions (W x H x D)

Package size varies from 6U x 17" x 16" to a 9U x 19" x 16" modular configuration, depending on input/output combination required.

Chassis-mount and rack mount versions are available at the same price

Weight

From 20 kg (43 lb) to 42kg (90lb), depending on the modular configuration

Connections

Input: terminal-block or threaded studs
Outputs: terminal block

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice

Enhancements to these general specifications can be accommodated upon request. Specifications are subject to change

Designer and manufacturer of quality ac-dc power supplies and battery chargers, converters, inverters, dc-output UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility.



ABOPULSE ELECTRONICS LTD

110 Walgreen Road
Ottawa, Ontario. K0A 1L0. CANADA
Tel: +1-613-836-3511 Fax: +1-613-836-7488
E-mail: absopulse@absopulse.com
<http://www.absopulse.com>