

500VA Rugged, Industrial Quality Fan Cooled Inverter with Sine Wave Output CSI 500F-FXW Series



- Sinusoidal output voltage
- Rugged field-proven design
- Filtered input
- Cooling by internal fans
- Full electronic protection
- Field-proven design topology

This rugged, industrial quality DC/AC inverter utilizes field proven, microprocessor controlled high frequency PWM technology to generate the required output power with pure sine wave output voltage. It is a mature design with a track record in numerous applications. The DC/DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC/AC inverter to generate the required AC output. High frequency conversion enables a compact construction, low weight and high efficiency. The input and output are filtered for low noise. High quality built-in fans provide sufficient airflow for operation without de-rating within the specified temperature range. The fans draw air into the unit, and exhaust at the opposite side of the unit. All heat generating components are installed on aluminum heatsink blocks which are thermally connected to the base plate. This also ensures exceptional mechanical ruggedness. Conformal coating provides protection against humidity and airborne contaminants. Full electronic protection, low component count, large design headrooms, and the exclusive use of components with established reliability contribute to a high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

24V, 36V, 48V or 125Vdc
±15% are standard
Consult factory for other inputs, and range

Input Protection

Inrush current limiting
Varistors
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

1700Vdc input to chassis/output or corresponding to the voltage requirements
Output neutral is connected to the chassis on the terminal block. The jumper can be removed for floating output

Standards

Designed to meet
C22.2 No. 107.1 - 01,
UL 458 and EN60950-1

EMI

EN 55022 Class A
with margins

Output Voltage

115Vac/4.3A continuous,
60Hz or 400Hz or
230Vac/2.17A continuous, 50Hz
Isolated floating output optional
Consult factory for other output requirements

Output Wave Form

Sinusoidal

Total Harmonic Distortion

Less than 5% at full load

Line/Load Regulation

± 3% from no load to full load

Load Crest Factor

2 at 90% load

Output Noise

High frequency ripple is better than 500mVrms (20MHz BW)

Output Overload Protection

Current limiting with short circuit protection
Thermal shutdown with automatic recovery in case of insufficient cooling

Output Overvoltage Protection

140Vac (for 115Vac output) or
280Vac (for 230Vac output) by
internal supply voltage limiting

Efficiency

Typically 80% at full load
depending on input/output
configuration

Operating Temperature Range

0°C to +50°C for full specification
Extended temperature ranges
available

Temperature Drift

0.05% per °C over operating
temperature range

Cooling

By built-in high quality fans and
conduction via baseplate

Environmental Protection

Basic ruggedizing
Conformal coating
Heavy ruggedizing available
as option

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing

MTBF

Min. 130,000 hours at 45°C
fans excluded
Demonstrated MTBF is
significantly higher

Indicators

None

Control Input

None
Remote shutdown as option

Alarm Output

None
Option: output fail alarm (Form C)

Package/Dimensions (WxHxL)

FXW: 185 x 66 x 358 mm
7.3" x 2.6" x 14.1" including
connectors and flanges

Weight

3kg (6.6 lbs)

Connections

12-pole barrier type terminal
block with 3/8" spacing

RoHS Compliance

Compliant

Warranty

Two years subject to application
within good engineering practice

Terminal Block Pin-out

AC OUTPUT							GND		VDC INPUT		
L1	L2	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	⊥	—	+	+	
1	2	3	4	5	6	7	8	9	10	11	12

Please note that ABSOPULSE power supplies are designed and built to customer specifications. The specifications on this data sheet are generic and will vary depending on input/output configuration and other customer requirements. Generic specifications are subject to change.

Designer and manufacturer of quality ac-dc power supplies and battery chargers, converters, inverters, dc-output UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility.



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: absopulse@absopulse.com | <http://www.absopulse.com>