

250W, Rugged, Industrial Quality DC/DC Converter with High DC-output Voltage DCW 280-F1W Series



- Rugged industrial quality
- Two regulated outputs
- Conduction/convection cooled – no fan
- Full electronic protection
- Field-proven design concept

This rugged, industrial quality, DC/DC converter generates up to 250W continuous output power, depending on the input/output configuration. The design is based on the field-proven DCW 150 series topology, which has a track record in numerous applications. All heat generating components are installed on aluminum heatsink blocks which are thermally connected to the base plate. This also provides exceptional mechanical ruggedness. Additional cooling is achieved by natural convection through the cooling slots. Conformal coating provides protection against humidity and airborne contaminants. Full electronic protection, low component count, large design headroom and the exclusive use of components with established reliability contribute to a high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

24V, 36V, 48V, 125V, 250Vdc
Consult factory for other
input voltages and ranges

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified
minimum input will not damage
the unit

Isolation

Corresponding to input/output
voltage:
1500Vdc input to chassis
2250VDC input to output
500VDC min. output to chassis
500VDC min. between outputs

Standards

Designed to meet EN 60950-1
and related standards

EMI

EN55022 Class A with margins
conducted and radiated

Switching Frequency

47KHz \pm 2KHz

Output Voltage

250V, 300V or 350Vdc
Total output power 250W
continuous
Output is floating, either terminal
can be grounded

Redundancy diode

None
Available as option

Line/Load Regulation

\pm 1% combined from no load to full
load

Dynamic Response

Max 5% voltage deviation for 10%
to 50% load step, with better than
1msec recovery time

Output Ripple/Noise

Better than 1% of output voltage
peak to peak or 0.2% RMS of the
output voltage (20MHZ BW)

Overload Protection

Rectangular current limiting with
cycling-type short circuit
protection

Output Overvoltage Protection

Double regulator loop

Efficiency

Typically 85% at full load depending
on input/output configuration

Operating Temperature

0°C to 50°C for full specification
Extended temperature ranges
available

Temperature Drift

0.03% per °C over operating
temperature range

Cooling

Conduction via base plate to
customer heat-sink or chassis and
natural convection

Environmental Protection

Basic ruggedizing
Heavy ruggedizing and conformal
coating is available as option

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 – 95% non-condensing

MTBF

140,000 hours @45°C
Demonstrated MTBF is
significantly higher

Indicators

Green output ON LED visible
through cooling slots

Control Input

None

Alarm Output

None on standard version
Available as option

Package/Dimensions (W x H x L)

F1W: 163 x 51 x 200 mm
(6.4" x 2" x 7.9") including
terminal block and flanges
Mounting holes are clear

Weight

1.4 kg (3 lbs)

Connections

12-pole barrier-type terminal
block, 3/8" spacing

RoHS

Compliant

Warranty

Two years subject to application
within good engineering practice

The specifications on this data sheet are generic and are subject to change. Enhancements to these specifications can be provided upon request.

OEM of industrial & railway quality AC/DC power supplies and battery chargers, DC/DC converters, DC-AC sine-wave inverters, phase and frequency converters, DC-output UPS systems and complete power systems in 19" & 23" racks since 1982. Custom or standard. ABSOPULSE is a BAPT-approved facility.



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: absopulse@absopulse.com | <http://www.absopulse.com>