

50W, Rugged DC/DC Converter for Railway and other Harsh Environments

DCW 50R-F0 Series



- Field-proven rugged design
- For train and mobile applications
- EN50155 input ranges
- Conduction/convection cooled
- Full electronic protection
- Wide selection of input/output combinations

This rugged, railway quality power converter utilizes field-proven technology to generate the required output power. It is a mature design with a track record in numerous applications. Cooling is by conduction via baseplate. Additional cooling is achieved by natural convection through the cooling slots. All heat generating components are installed on aluminum heatsink blocks which are thermally connected to the base plate. This also provides exceptional mechanical ruggedness. Conformal coating provides protection against humidity and airborne contaminants. Full electronic protection, low component count, large design headroom and the exclusive use of components with established reliability contribute to a high MTBF. The series meets the requirements of EN50155 for electronic equipment used on railway rolling stock. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage (nominal/range)

24Vdc (15 - 34V)
48Vdc (29 - 67V)
72Vdc (43 - 101V)
96Vdc (58 - 135V)
110Vdc (66 - 154V)
Other inputs on request

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

1500Vdc input to chassis
3000Vdc input to output
1500Vdc output to chassis

Standards

Designed to meet EN60950-1 and EN50155

Immunity

Meets criteria as requested in EN50155 and EN50121-3-2 according to:
EN 61000-4-2 (ESD)
EN 61000-4-3 (RF Immunity)
EN 61000-4-4 (Fast Transients)
EN 50155 (Surge)
EN 61000-4-6 (Conducted Imm.)
EN 50155 (Voltage Variations)

EMI

EN50121-3-2

Switching Frequency

47kHz \pm 2kHz

Output Voltage/Current

12V/4A, 24V/2A, 48V/1A or 110V/0.45A are standard.
Other voltages and higher power rating available on request

Redundancy diode

None
Available on request

Line/Load Regulation

\pm 1% combined from no load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHz BW)

Overload Protection

Rectangular current limiting with hiccup type short circuit protection

Output Overvoltage Protection

Double regulator loop.
Transzorb installed across the output

Efficiency

80 to 90% at full load depending on input/output configuration

Operating Temperature

-25 to +70°C cold-plate temperature range for full specification

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Conduction via base plate to customer heat-sink or chassis and natural convection

Environmental Protection

Ruggedizing
Conformal coating
Heavy ruggedizing available on request

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing

MTBF

Min. 150,000 hours @45°C
Demonstrated MTBF is significantly higher

Indicators

None

Control Input

None

Alarm Output

None

Package/Dimensions (W x H x L)

F0: 94 x 48 x 160 mm (3.7" x 1.9" x 6.3") including terminal block and flanges
Mounting holes are clear.

Weight

0.55kg (1.2 lbs)

Connections

6-pole barrier-type terminal block, 3/8" spacing

RoHS

Compliant

Warranty

Two years subject to application within good engineering practice

Standard Terminal Block Pin-Out

OUTPUT			INPUT		
-	+	NOT USED	GND	+	-
1	2	3	4	5	6

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications are subject to change.

Designer and manufacturer of quality ac-dc power supplies and battery chargers, converters, inverters, dc-output UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility.



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario | K0A 1L0 | CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: absopulse@absopulse.com | <http://www.absopulse.com>