

300W, IP66-Rated, Rugged Industrial, AC-DC Power Supply with Wide Input Ranges HBC 65-D3 Series (IP66)

- Packaged in waterproof enclosure
- Internal module ruggedized and conformal coated
- Single regulated output
- Full electronic protection
- Field-proven design
- N+1 redundancy available



The rugged industrial quality AC-DC power supplies utilize field proven topology to generate the required output power. They are packaged in waterproof, rugged, die cast aluminum IP66 enclosures. The input and output are via sealed cable glands, circular connectors or custom connections. The internal boards are ruggedized and conformal coated for immunity to high levels of shock and vibration. Cooling is by internal conduction to the walls of the IP66 enclosure and by baseplate to an external chassis or cabinet wall, with additional convection via the outside surface. If installed on a heat-sinking surface, cooling is further enhanced and the converters achieve higher output power. Optional built-in redundancy diode allows for parallel and N+1 operation. Full electronic protection, low component count, large design headroom, and the use of components with established reliability contribute to high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

115Vac (95 – 132V) 47 - 63Hz
230Vac (190 – 264V) 47 - 63Hz
250Vdc (210 – 290V)
300Vdc (250 – 350V)
Other voltages on request

Input Protection

Inrush current limiting
Varistor
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

2250VDC input to chassis
4300VDC input to output
8mm spacing
500VDC output to chassis

Standards

Designed to meet EN60950-1 and corresponding UL and CSA standards

EMI

EN55022 Class A with margins or as required

Switching Frequency

55KHz ±3KHz

Hold Up Time

Minimum 10ms at full load for 5% drop of output voltage at nominal input

Output Voltage/Current

12Vdc, 24Vdc, 48Vdc or 125Vdc
300W continuous output power
Output is floating; either terminal can be grounded
Other outputs and increased output power on request

Redundancy Diode

Installed on request

Line/Load Regulation

± 1% combined from zero load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple / Noise

Less than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHz BW)

Output Overload Protection

Rectangular current limiting with short-circuit protection (no hiccup)
Thermal shutdown in case of insufficient cooling (self resetting)

Output Overvoltage Protection

Double regulator loop completely stable and independent of main loop

Efficiency

Output voltage dependent.
Typically 80% at full load

Operating Temperature Range

-25 °C to 55 °C for full specification
Extended temperature ranges available on request

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Conduction to customer heat-sink or chassis and by additional natural convection via the surface of the IP66 enclosure

Environmental Protection

IP66 enclosure
Internal module: Ruggedized and conformal coated
Potting of the internal module is also available

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5-100% condensing

MTBF

150,000 at 45°C
Demonstrated MTBF is significantly higher

Indicators

None

Control Input

None

Alarm Output

Not installed
Optional output Fail Alarm

Package/Dimensions (L x W x H)

D3: 360 x 160 x 90 mm
14.2" x 6.3" x 3.5"
D3 with baseplate:
406 x 160 x 94 mm
(16" x 6.3" x 3.7")

Weight

Approx. 4.6 kg (10 lb)

Connections

Internal barrier-type terminal block accessible via sealed cable glands.
Optional connectors instead of cable glands

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice

The specifications on this data sheet are generic and are subject to change. Enhancements to these specifications can be provided upon request.

OEM of industrial & railway quality AC/DC power supplies and battery chargers, DC/DC converters, DC-AC sine-wave inverters, phase and frequency converters, DC-output UPS systems and complete power systems in 19" & 23" racks since 1982. Custom or standard. ABSOPULSE is a BABT-approved facility



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario | K0A 1L0 | CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: absopulse@absopulse.com | <http://www.absopulse.com>