

## 100W, Encapsulated AC/DC Power Supply for Heavy Duty Applications PWI 100 Series-P99L



- Rugged, field proven design
- Conduction cooling
- Fully encapsulated
- Full electronic protection
- Universal input ranges

This fully encapsulated, rugged, industrial quality AC-DC power supply uses field-proven technology to generate 100W output power. It is a mature product with a track-record in numerous applications. The unit is entirely potted with a thermally conductive MIL-grade silicon rubber compound to provide immunity to shock, vibration and humidity. It is conduction cooled via a base-plate to a heat-sinking surface. Full electronic protection, low component count, large design headroom, and the use of components with established reliability ensure high MTBF. The unit is suitable for transportation, mining, oilrigs, military and other harsh environments. The converter is manufactured at our plant under strict quality control. Versions that are designed to meet EN 50155 railway specifications are also available.

### SPECIFICATIONS

#### Input Voltage

Universal input  
95Vac - 264Vac, 47-63Hz  
DC-input also available  
Consult factory for other voltages

#### Input Protection

Inrush current limiting  
Varistor  
Internal safety fuse  
Line to GND varistor upon request  
Lower voltage than the specified minimum input will not damage the unit

#### Isolation

2250VDC input to chassis  
4300VDC input to output;  
8mm spacing  
500VDC output to chassis

#### Standards

Designed to meet EN60950-1 and corresponding UL and CSA standards

#### EMI

EN55022 Class A with margins

#### Switching Frequency

47kHz ± 2kHz

#### Hold-Up Time

Minimum 5ms at full load for 5% drop of output voltage at 120V AC input.

#### Output Voltage/Current

12Vdc/8A, 24Vdc/4A or 48Vdc/2A  
Output is floating, either terminal can be grounded  
Consult factory for other voltages

#### Redundancy Diode

None

#### Line/Load Regulation

±1% combined from zero load to full load

#### Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

#### Output Ripple/Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage. (20MHz BW)

#### Output Overload Protection

Rectangular current limiting with short-circuit protection (hiccup type)

#### Output Over-voltage Protection

Double regulator loop completely stable and independent of main regulator loop

#### Efficiency

Output is voltage dependent.  
Typically 80% at full load

#### Operating Temperature Range

-40°C to +70°C cold-plate temperature for full specification

#### Temperature Drift

0.03% per °C over operating temperature range.

#### Cooling

Conduction via base plate to customer heatsink or chassis

#### Environmental Protection

Full encapsulation with thermally conductive silicon potting compound with UL94V-0 flammability rating.  
Meets environmental criteria as requested in MIL-810 C, D

#### Shock/Vibration

IEC 61373 Cat 1 A&B

#### MTBF

180,000 hours @ 45 °C  
Demonstrated MTBF significantly higher

#### Indicators

None

#### Control Input

None

#### Alarm output

None

#### Package/Dimensions (W x H x L)

P99L: 81 x 61 x 156mm (3.2" x 2.4" x 6.2") including terminal blocks and flanges.  
Mounting holes are clear.

#### Weight

0.95 kg (2 lb)

#### Connections

6 pole barrier type terminal block, 3/8" spacing. Snap-on cover available.

#### RoHS Compliance

Compliant

#### Warranty

Two years subject to application within good engineering practice

#### Terminal Block Pin-out

DC OUTPUT			AC INPUT		
-	+	NOT USED	⏏	PH	N
1	2	3	4	5	6

**Enhancements to these general specifications and customizing can be accommodated upon request. Specifications are subject to change.**

*Designer and manufacturer of quality ac-dc power supplies and battery chargers, converters, inverters, dc-output UPS systems, and complete rack mount systems in 19" or 23" racks. Custom or standard. ABSOPULSE is a BABT-approved Facility.*



#### ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: [absopulse@absopulse.com](mailto:absopulse@absopulse.com) | <http://www.absopulse.com>