

**200W, Rugged DC/DC Converter for Redundant Operation in
Railway and other Heavy Duty Environments
RWD 200-P200L, RWD 200-P200X Series**

- Rugged, field-proven design
- Built-in redundancy diode
- Complete encapsulation
- Wide temperature range
- Full electronic protection
- EN 50155 input ranges



P200L (side flanges)



P200X (flanges at each end)

This fully encapsulated, railway quality power converter utilizes field-proven technology to generate the required output power. A built-in output separation diode allows for redundant operation. It is a mature design with a track record in numerous applications. The unit is entirely potted with a thermally conductive MIL-grade silicon rubber compound which provides protection from moisture and other contaminants, as well as immunity to shock and vibration. Cooling is by conduction via a base plate to a heatsinking surface. Full electronic protection, low component count, large design headroom and the exclusive use of components with established reliability contribute to a high MTBF. The unit meets the requirements of EN50155 for electronic equipment used on railway rolling stock. It is manufactured at our plant under strict quality control. Customized versions are also available.

SPECIFICATIONS

Standard Input Voltages

24Vdc (14.4 – 34V)
36Vdc (22 – 51V)
48Vdc (29 – 67V)
72Vdc (43 – 101V)
96Vdc (58 – 135V)
110Vdc (66 – 154V)
Consult factory for other voltages and ranges

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than specified minimum input will not damage unit

Isolation

1500Vdc input to chassis
3000Vdc input to output
1500Vdc output to chassis

Standards

Designed to meet EN60950-1, EN50155

Immunity

Meets criteria of EN50155 and EN50121-3-2 according to the following standards:
EN 61000-4-2 (ESD)
EN 61000-4-3 (RF Immunity)
EN 61000-4-4 (Fast Transients)
EN 50155 (Surge)
EN 61000-4-6 (Conducted Imm.)
EN 50155 (Voltage Variations)

EMI

EN 50121-3-2

Switching Frequency

80kHz ±5kHz

Output Voltage/Current

12Vdc/16A or 24Vdc/8A
Output is floating, either terminal can be grounded
Consult factory for other voltages

Redundancy Diode

Built-in redundancy diode

Line/Load Regulation

±1.5% combined from zero load to full load including redundancy diode

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Less than 1% peak-to-peak or 0.2% RMS of the output voltage (20MHz BW)

Output Overload Protection

Rectangular current limiting with hiccup type short-circuit protection
Thermal shutdown with automatic recovery in case of insufficient cooling

Output Overvoltage Protection

Second regulator loop completely stable and independent of main regulator loop
Transzorb clamp

Efficiency

80 to 90% depending on input/output configuration

Operating Temperature Range

-40 to +70°C cold plate temperature for full specification

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Conduction via base plate to customer chassis or heat-sink

Environmental Protection

Full encapsulation with thermally conductive silicon potting compound with UL94V-0 flammability rating.
Meets environmental criteria as requested in MIL-810 C, D

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 – 95% non-condensing

MTBF

150,000 hours @ 45 °C
Demonstrated MTBF is significantly higher

Indicators

None

Control Input

None

Alarm Output

Output Fail Alarm
Fail Open
Referenced to output return

Package/Dimensions (W x H x L)

P200L (side flanges):
94 x 60 x 230 mm
3.7" x 2.4" x 9.1"
P200X (flanges at each end):
70 x 57 x 253 mm
2.7" x 2.2" x 9.9"
Dimensions include terminal block and flanges
Mounting holes are clear

Weight

1.3kg (2.8 lb)

Connections

5-pole barrier-type terminal block with 3/8" spacing
Terminal block cover can be provided upon request

RoHS Compliance

Compliant

Warranty

Two years subject to application within good engineering practice

Terminal Block Pin-Out

OUTPUT		ALARM	INPUT	
+	-	F/O	+	-
1	2	3	4	5

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications subject to change.

Designer and manufacturer of quality ac-dc power supplies and battery chargers, converters, inverters, dc-output UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. ABSOPULSE is a ABT-approved Facility.



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario | K0A 1L0 | CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: absopulse@absopulse.com | <http://www.absopulse.com>