

50W, Rugged, Encapsulated DC-DC Converter for Heavy-duty Applications PDC 50-P99H Series



- Rugged, field-proven design
- Fully encapsulation
- Conduction cooling
- Full electronic protection
- Wide temperature range
- Wide input ranges

This fully encapsulated, industrial quality, DC-DC converter uses field-proven technology to generate the required output power. It has an excellent track record in numerous heavy-duty applications. The unit is entirely potted with a thermally conductive MIL-grade silicon rubber compound which provides protection from moisture and other contaminants, as well as immunity to shock and vibration. Cooling is via base plate by conduction. The unit is designed for continuous operation at 70°C with installation on an appropriate size heat sinking surface. Full electronic protection, low component count, large design headroom and the exclusive use of components with established reliability contribute to a high MTBF. The unit is suitable for transportation, mining, oilrigs, military and other harsh environments. The converter is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

24Vdc (21V – 30V)
48Vdc (42 – 60V)
125Vdc (95 - 140V)
Consult factory for other voltages and ranges, including for railway

Input Protection

Inrush current limiting
Varistor
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

According to input/output voltage, but minimum of:
1000VDC input to chassis
1500VDC input to output
500VDC output to chassis

Standards

Designed to meet EN60950-1 and corresponding UL and CSA standards

EMI

EN 55032 Class A with margins

Switching Frequency

55kHz ±3kHz

Output Voltages

12Vdc, 24Vdc, 36Vdc, 48Vdc or 72Vdc
Output is floating; either terminal can be grounded.
Consult factory for other voltages

Redundancy Diode

Not installed
Available on custom versions

Line/Load Regulation

±1% combined from zero load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple / Noise

Better than 1% of output voltage peak to peak or 0.2% Vrms (20MHz BW)

Output Overload Protection

Rectangular current limiting with short-circuit protection

Output Overvoltage Protection

Second regulator loop

Efficiency

Output is voltage dependent.
Typically 80% at full load

Operating Temperature Range

-40°C to 70°C cold-plate temperature for full specification

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Conduction cooling via base plate to customer chassis or heat-sink

Environmental Protection

Full encapsulation with thermally conductive silicon potting compound with UL94V-0 flammability rating.

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing

MTBF

150,000 hours @ 45°C
Demonstrated MTBF is significantly higher

Indicators

None

Control Input

None

Alarm Output

None

Dimensions (W x H x L)

P99H: 82 x 63 x 157 mm
3.2" x 2.5" x 6.2" including terminal block and flanges
Mounting holes are clear

Weight

0.8 kg (1.5 lb)

Connections

6-pole barrier-type terminal block, 3/8" spacing

RoHS Compliance

Compliant

Warranty

Two years subject to application within good engineering practice

Terminal Block Pin-out

OUTPUT			INPUT		
-	+	N/A	GND	-	+
1	2	3	4	5	6

Please note that ABSOPULSE power supplies are designed and built to customer specifications. The specifications on this data sheet are generic and will vary depending on input/output configuration and other customer requirements. Generic specifications are subject to change.

Designer and manufacturer of quality ac-dc power supplies and battery chargers, converters, inverters, dc-output UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility.



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

E-mail: absopulse@absopulse.com | <http://www.absopulse.com>