

1000W, Rugged, Industrial Quality, AC-DC Power Supply with PFC-input PFH 65F-F3W Series



- Fixed frequency power factor correction (PFC)
- Rugged industrial quality
- Cooling by internal fans
- Single phase input
- Full electronic protection
- N+1 redundancy available as option

This rugged, industrial quality AC-DC power supply with PFC input uses field proven PFQ 65 topology to deliver the required output power. An optional built-in redundancy diode allows for parallel connection to achieve higher output power or N+1 redundancy, and also makes the unit suitable for battery charging applications. Cooling is by high quality built-in fans which draw air into the unit, and by conduction via the baseplate. All heat generating components are installed on aluminum heatsink blocks which are thermally connected to the base plate. This also ensures exceptional mechanical ruggedness. Conformal coating provides protection against humidity and airborne contaminants. Full electronic protection, low component count, large design headroom and the exclusive use of components with established reliability contribute to a high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

95-264Vac, 47... 63Hz
Input current 13A max at 95V
Power Factor is better than 0.97 at full load for the entire input range.
Meets EN61000-3-2

Input Protection

Inrush current limiting
Varistor
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

2250VDC input to chassis
4300VDC input to output
8mm spacing
1300VDC output to chassis

Standards

Designed to meet EN60950-1 and related UL/CSA standards

EMI

EN 55032 Class A with margins

Switching Frequency

Input Stage: 80kHz \pm 5kHz
Output Stage: 55kHz \pm 3kHz

Hold Up Time

Min. 5ms at nominal input for 5% drop of the output voltage at any input

Output Voltage/Current

24Vdc/40A, 48Vdc/20A, 110Vdc/9A or 125Vdc/8A
Output is floating; either terminal can be grounded
Other outputs available on request

Redundancy Diode

Not installed
Available as an option

Line/Load Regulation

\pm 1% combined from zero load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHz BW)

Overload Protection

Rectangular current limiting with short-circuit protection (no hiccup)
Thermal shutdown in case of insufficient cooling (self-resetting)

Output Overvoltage Protection

Second regulator loop completely stable and independent of the main regulator loop

Efficiency

Output voltage dependent
Typically 80% at full load

Operating Temperature

0°C to 50°C cold plate temperature for full specification
Extended temperature range available

Temperature Drift

0.03% per °C over
Operating temperature range

Cooling

Forced air by two high quality built-in fans

Environmental Protection

Basic ruggedizing
Conformal coating

Shock/Vibration

IEC61373 Cat 1 A&B

Humidity

5-95% non-condensing

MTBF

130,000 hours @ 45°C (fans excluded)
Demonstrated MTBF is significantly higher

Indicators

None on standard version
Available as option

Control Input

None on standard version
Available as option

Alarm Outputs

None on standard version
Available as option

Package/ Dimensions (W x H x L)

F3W: 157 x 65 x 295 mm (6.2" x 2.5" x 11.6") including terminal block and flanges
Mounting holes are clear.

Weight

2.3kg (5 lbs)

Connections

12-pole barrier-type terminal block with 3/8" spacing

RoHS Compliance

Compliant

Warranty:

Two years subject to application within good engineering practice
Contamination related failures and shipping costs excluded.

Terminal Block Pin-out

DC OUTPUT						ALARM (OPTION)			AC INPUT		
NOT USED	NOT USED	+	+	-	-	FAIL OPEN	COM	FAIL CLOSED	GND	N	PH
1	2	3	4	5	6	7	8	9	10	11	12

Please note that ABSOPULSE power supplies are designed and built to customer specifications. The specifications on this data sheet are generic and will vary depending on input/output configuration and other customer requirements. Generic specifications are subject to change

Designer and manufacturer of quality converters, inverters, UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. ABSOPULSE is a BABT-approved Facility



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario | KOA 1L0 | CANADA

Tel: +1-613-836-3511 | Fax: +1-613-836-7488

<https://absopulse.com/contact> | <https://www.absopulse.com.com>