

200VA Rugged, Industrial Quality DC-AC Inverter with Sine Wave Output CSI 200-F3 Series



- Sinusoidal output voltage
- Rugged, field-proven design
- Filtered input and output
- Conduction/convection cooling
- Full electronic protection

This rugged DC-AC inverter uses field proven, microprocessor controlled high frequency PWM technology to generate the required output with pure sine wave output. The design is based on mature technology with a track record in numerous applications. The input and output are filtered for low noise. The use of high frequency conversion enables a compact construction, low weight and high efficiency. Cooling is by conduction via baseplate. Additional cooling is achieved by natural convection through the cooling slots. All heat generating components are installed on aluminum heatsink blocks which are thermally connected to the base plate. This also provides exceptional mechanical ruggedness. Conformal coating provides protection against humidity and airborne contaminants. Full electronic protection, low component count, large design headroom and the exclusive use of components with established reliability contribute to a high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

24V, 36V, 48V, 125Vdc
± 15% are standard
Consult factory for other inputs

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

Compliant to input and output voltages according to the corresponding standards
Floating output

Standards

Designed to meet
C22.2 No. 107.1 - 01,
UL 458 and EN60950-1

EMI

EN55032 Class A with margins

Output Voltage

115Vac/1.7Arms/60Hz or 400Hz;
230Vac/0.86Arms/50Hz
200VA continuous
Isolated floating output
Consult factory for other output requirements

Output Wave Form

Sinusoidal

Total Harmonic Distortion

Less than 5% at full load

Line/Load Regulation

±2% from no load to full load

Load Crest Factor

3 at 90% load

Output Noise

High frequency ripple is better than 500mVrms (20MHz BW)

Output Overload Protection

Current limiting with short circuit protection

Output Overvoltage Protection

Output voltage is limited by internal supply voltage

Efficiency

Input voltage dependent
Typically 80% at full load

Operating Temperature Range

0° C to +50° C for full specification
Extended temperature ranges available

Temperature Drift

0.05% per °C over operating temperature range

Cooling

Conduction and natural convection
The unit must be installed on heatsinking surface such as chassis or cabinet wall for full power

Environmental Protection

Basic ruggedizing
Conformal coating

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing

MTBF

130,000 hours at 45°C
Demonstrated MTBF is significantly higher

Indicators

None

Control Input

None

Alarm Output

None
Optional output fail alarm (Form C)

Package/Dimensions (W x H x L)

F3: 132mm x 62mm x 290 mm
(5.2" x 2.5" x 11.4")
Includes flanges, excludes terminal block
Mounting holes are clear

Weight

2 kg (4.4 lb)

Connections

12-pole barrier type terminal block with 3/8" spacing

RoHS Compliance

Compliant

Warranty

Two years subject to application within good engineering practice.

Terminal Block pin-out

VAC OUTPUT					VDC INPUT						
NOT USED	L1	L2	NOT USED	GND	NOT USED	NOT USED	NOT USED	-	-	+	+
1	2	3	4	5	6	7	8	9	10	11	12

ABSOPULSE power supplies are designed and built to customer requirements. The specifications on this data sheet are generic guidelines only and are subject to change.

OEM of industrial and railway quality DC-DC converters, AC-DC power supplies and battery chargers, DC-AC sine-wave inverters, phase and frequency converters, DC-output UPS systems and complete power systems in 19" and 23" racks since 1982. Custom or standard. ABSOPULSE is a BABT-approved Facility.



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA
Tel: +1-613-836-3511 | Fax: +1-613-836-7488

<https://absopulse.com/contact> | <https://www.absopulse.com>