

280W, Rugged Dual-output, Industrial Quality DC-DC Converter with Wide Input Range DCW 282-F1W Series



- Rugged industrial quality
- Two regulated outputs
- Wide DC-input voltage range
- Conduction/convection cooled – no fans
- Field-proven design
- Full electronic protection

This rugged, industrial quality, dual-output DC-DC converter generates up to 280W continuous output power, depending on the input/output configuration. The design is based on the field proven DCW 150 topology. The unit has two fully independent regulated isolated outputs. Cooling is by conduction via baseplate. Additional cooling is achieved by natural convection through the cooling slots. All heat generating components are installed on aluminum heatsink blocks which are thermally connected to the base plate. This also provides exceptional mechanical ruggedness. Conformal coating provides protection against humidity and airborne contaminants. Full electronic protection, low component count, large design headroom and the exclusive use of components with established reliability contribute to a high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

24Vdc (21-30V)
36Vdc (31-41V)
48Vdc (42-56V)
125Vdc (105-145V)
250Vdc (205-300V)
Wide input range models:
20 - 60Vdc or 65 - 160Vdc
Consult factory for other
input voltages and ranges

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified
minimum input will not damage
the unit

Isolation

Corresponding to input/output
voltage:
1500Vdc input to chassis
2250VDC input to output
500VDC min. output to chassis
500VDC min. between outputs

Standards

Designed to meet EN62368-1
and related standards

EMI

EN55032 Class A with margins

Switching Frequency

47kHz \pm 2kHz

Output Voltage

V1: Any voltage 5V to 125Vdc
V2: Any voltage 5V to 125Vdc
The current on each output is
limited to 10A
Both outputs are fully regulated
The outputs are floating; either
terminal can be grounded
Returns are separated.

Redundancy diode

None
Available as option

Line/Load Regulation

\pm 1% combined from no load to full
load on both outputs

Dynamic Response

Max 5% voltage deviation for 10%
to 50% load step, with better than
1msec recovery time

Output Ripple/Noise

Better than 1% of output voltage
peak to peak or 0.2% RMS of the
output voltage (20MHz BW)

Overload Protection

Rectangular current limiting with
hiccup type short-circuit
protection (hiccup mode) on both
outputs. The other output is not
affected. Thermal shutdown with
automatic recovery in case of
insufficient cooling

Output Overvoltage Protection

Double regulator loop and
transzors on both outputs

Efficiency

Typically 85% at full load depending
on input/output configuration

Operating Temperature

0°C to 50°C for full specification
Extended temperature ranges
available

Temperature Drift

0.03% per °C over operating
temperature range

Cooling

Conduction via base plate to
customer heat-sink or chassis and
natural convection

Environmental Protection

Basic ruggedizing
Conformal coating

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 – 95% non-condensing

MTBF

140,000 hours @45°C
Demonstrated MTBF is
significantly higher

Indicators

Green output ON LED on both
outputs, visible through cooling
slots

Control Input

None

Alarm Output

None on standard version
Available as option

Package/Dimensions (W x H x L)

F1W: 163 x 51 x 198 mm
6.43" x 2" x 7.78" Includes
baseplate, excludes terminals.
Mounting holes are clear.

Weight

1.4 kg (3 lbs)

Connections

12-pole barrier-type terminal
block, 3/8" spacing

RoHS

Compliant

Warranty

Two years subject to application
within good engineering practice

ABSOPULSE power supplies are designed and built to customer requirements. The specifications on this data sheet are generic guidelines only and are subject to change.

OEM of industrial and railway quality DC-DC converters, AC-DC power supplies and battery chargers, DC-AC sine-wave inverters, phase and frequency converters, DC-output UPS systems and complete power systems in 19" and 23" racks since 1982. Custom or standard. ABSOPULSE is a BABT-approved Facility.



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA
Tel: +1-613-836-3511 | Fax: +1-613-836-7488

<https://absopulse.com/contact> | <https://www.absopulse.com>