

300VA Rugged, Industrial Quality DC-AC Sine Wave Inverter CSI 300-FX Series



- Sinusoidal output voltage
- Rugged field-proven design
- Filtered input
- Conduction/convection cooling
- Full electronic protection
- Field-proven design topology

This rugged, industrial quality DC-AC inverter utilizes field proven, microprocessor controlled high frequency PWM technology to generate the required output power with pure sine wave output voltage. It is a mature design with a track record in numerous applications. The DC-DC input stage boosts the input voltage to a higher DC voltage, which feeds the DC-AC inverter to generate the required AC output. High frequency conversion enables compact construction, low weight and high efficiency. The input and output are filtered for low noise. Cooling is by conduction via baseplate. Additional cooling is achieved by natural convection through the cooling slots. All heat generating components are installed on aluminum heatsink blocks which are thermally connected to the base plate. This also ensures exceptional mechanical ruggedness. Conformal coating provides protection against humidity and airborne contaminants. Full electronic protection, low component count, large design headroom, and the exclusive use of components with established reliability contribute to a high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

24V, 36, 48V or 125Vdc $\pm 15\%$
Consult factory for other inputs, and range

Input Protection

Inrush current limiting
Varistors
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

1000Vdc input to chassis
3000Vdc input to output
2250Vdc output to chassis
Floating output

Standards

Designed to meet
C22.2 No. 107.1 - 01,
UL 458 and EN62368-1

EMI

EN55032 Class A with margins

Output Voltage

115Vac/2.6A/60Hz or 400Hz
230Vac/1.3A/50Hz
300VA continuous
Isolated floating output
Consult factory for other output requirements

Output Wave Form

Sinusoidal

Total Harmonic Distortion

Less than 5% at full load

Line/Load Regulation

$\pm 2\%$ from no load to full load

Load Crest Factor

2 at 90% load

Output Noise

High frequency ripple is better than 500mVrms (20MHz BW)

Output Overload Protection

Current limiting with short circuit protection
Thermal shutdown with automatic recovery in case of insufficient cooling

Output Overvoltage Protection

By internal supply voltage limiting at 30Vac

Efficiency

Typically 80% at full load

Operating Temperature Range

0°C to +50°C for full specification
Extended temperature ranges available

Temperature Drift

0.05% per °C over operating temperature range

Cooling

Conduction via base plate to customer heatsink or chassis and by natural convection

Environmental Protection

Basic ruggedizing
Conformal coating
Heavy ruggedizing available as option

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing

MTBF

Min. 130,000 hours at 45°C fans excluded
Demonstrated MTBF is significantly higher

Indicators

None

Control Input

None
Remote shutdown as option

Alarm Output

None
Option: output fail alarm (Form C)

Package/Dimensions (W x H x L)

FX: 153 x 67 x 351 mm
6" x 2.63" x 13.8"
Includes flanges, excludes terminal block
Mounting holes are clear

Weight

2.2 kg (4.9 lb.)

Connections

12-pole barrier-type terminal block with 3/8" spacing

RoHS Compliance

Compliant

Warranty

Two years subject to application within good engineering practice

Terminal Block Pin-out

AC OUTPUT		ENABLE		ALARM			DC INPUT				
L1	L2	NOT USED	NOT USED	NOT USED	NOT USED	NOT USED	GND	-	-	+	+
1	2	3	4	5	6	7	8	9	10	11	12

ABSOPULSE power supplies are designed and built to customer requirements. The specifications on this data sheet are generic guidelines only and are subject to change. OEM of industrial and railway quality DC-DC converters, AC-DC power supplies and battery chargers, DC-AC sine-wave inverters, phase and frequency converters, DC-output UPS systems and complete power systems in 19" and 23" racks since 1982. Custom or standard. ABSOPULSE is a BABT-approved Facility.



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario, K0A 1L0, CANADA
Tel: +1-613-836-3511 | Fax: +1-613-836-7488

<https://absopulse.com/contact> | <https://www.absopulse.com>