


300W, IP66-Rated Rugged Industrial Quality DC-DC Converter BAP 65-D3 Series (IP66)

- Packaged in waterproof IP66 enclosure
- Internal module ruggedized and conformal coated
- Single regulated output
- Full electronic protection
- Rugged field-proven designs
- N+1 redundancy available



The rugged industrial quality DC-DC converters utilize field proven topology to generate the required output power. The units are packaged in rugged, waterproof, die cast aluminum IP66 enclosures. The input and output are via sealed cable glands, circular connectors or custom connections. The internal boards are ruggedized and conformal coated for immunity to high levels of shock and vibration. Cooling is by internal conduction to the walls of the IP66 enclosure and by baseplate to an external chassis or cabinet wall, with additional convection via the outside surface. If installed on a heat-sinking surface, cooling is further enhanced and the converters achieve higher output power. Optional built-in redundancy diode allows for parallel and N+1 operation. Full electronic protection, low component count, large design headroom, and the use of components with established reliability contribute to high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage 24Vdc (21-29V) 48Vdc (42-56V) 125Vd (105-145V) For 12Vdc and other input voltages, consult factory	Output Voltage 12Vdc, 24Vdc, 48Vdc or 125Vdc 300W continuous output power Output is floating; either terminal can be grounded Other outputs and increased output power on request	Efficiency Input/output voltage dependent. Typically 85% at full load	Indicators None
Input Protection Inrush current limiting Varistor Reverse polarity protection Internal safety fuse Lower voltage than the specified minimum input will not damage the unit	Redundancy Diode None Installed on request	Operating Temperature Range -25 °C to 55 °C for full specification Extended temperature ranges available on request	Control Input None Optional
Isolation According to input voltage minimum of: 1000VDC input to chassis, 1500VDC input to output, 500VDC output to chassis	Line/Load Regulation ±1% combined from zero load to full load	Temperature Drift 0.03% per °C over operating temperature range	Alarm Output Not installed Optional output Fail Alarm
Standards Designed to meet EN 62368-1 and related standards	Dynamic Response Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time	Cooling Conduction to customer heat-sink or chassis and by additional natural convection via the surface of the IP66 enclosure	Package/Dimensions (W x H x D) <i>Overall dimensions including mounting flanges/baseplate:</i> 160 x 94 x 406 mm 6.3" x 3.7" x 16" <i>Dimensions of enclosure body:</i> 160 x 90 x 360 mm 6.3" x 3.5" x 14.2"
EMI EN 55032 Class A with margins or as required	Output Ripple/Noise Less than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHz BW)	Environmental Protection IP66 enclosure Internal module: Ruggedized and conformal coated Potting of the internal module is also available	Weight Enclosure with internal module: (un-potted): 4.6 kg; 10 lb
Switching Frequency 55KHz ±3kHz	Output Overload Protection Rectangular current limiting with short-circuit protection (no hiccup) Thermal shutdown in case of insufficient cooling (self resetting)	Shock/Vibration IEC 61373 Cat 1 A&B	Connections Internal barrier-type terminal block accessible via sealed cable glands. Optional connectors instead of cable glands
	Output Overvoltage Protection Double regulator loop completely stable and independent of main loop	Humidity 5-100% condensing	RoHS Compliance Compliant
		MTBF 150,000 at 45°C Demonstrated MTBF is significantly higher	Warranty Two years subject to application within good engineering practice

ABSOPULSE power supplies are designed and built to customer requirements. The specifications on this data sheet are generic guidelines only and are subject to change.

OEM of industrial and railway quality DC-DC converters, AC-DC power supplies and battery chargers, DC-AC sine-wave inverters, phase and frequency converters, DC-output UPS systems and complete power systems in 19" and 23" racks since 1982. Custom or standard. ABSOPULSE is a BABT-approved Facility.



ABSOPULSE ELECTRONICS LTD

110 Walgreen Road, Ottawa, Ontario. K0A 1L0. CANADA
Tel: +1-613-836-3511 | Fax: +1-613-836-7488

<https://absopulse.com/contact> | <https://www.absopulse.com>